

qEV ZENCO PRO

(FOR cGMP-COMPLIANT
ENVIRONMENTS)



The qEV Zenco is an automated chromatography system developed specifically for purifying samples using the qEV2, qEV10, qEV100 and larger customised qEV columns. To facilitate production in cGMP-compliant environments, we propose the following enhancements to the standard qEV Zenco model, which will form the qEV Zenco Pro. Note that the proposed specifications are subject to change, and we welcome your feedback or any questions you may have.

Table 1: Product Compliance Information for both qEV Zenco Models

Safety	IEC/EN/UL 61010-1, CAN/CSA-C22.2. No. 61010.12
EMC (Electromagnetic compatibility)	IEC/EN 61326-1, US 47 CFR part 15, Subpart B, Class A
Environment	RoSH2&3, REACH, WEEE

Table 2: cGMP Compliance Information for the qEV Zenco Pro

Software	21 CFR part 11
Material specifications of wetted parts (i.e., wetted parts of components that come into direct contact with process fluids or product)	USP class VI or ISO 10993, 21 CFR 177, animal origin free or in compliance with EMA/410/01, Quartz glass, Fused silica, Borosilicate glass to ASTM E483 Type 1 Class A, Stainless steel 316L ASME-BPE

Table 3: Specifications of Key Components

	qEV Zenco (standard)	qEV Zenco Pro (for cGMP-compliant environments)
Regulatory requirements	See electrical compliance information above	See electrical compliance and cGMP compliance information above
Shell	Powder coated steel	Stainless steel
Device-PC connection	USB-C	USB-C
Screen	No	Yes
TFF integrated	No	No
Inlet valve	Rotary valves 8 inlets/1 outlet OD: 3.175 mm (1/8"); ID: 1.59 mm PTFE tubing	Diaphragm valves 8 inlets/1 outlet OD: 3.175 mm (1/8); ID: 1.59 mm PTFE tubing
Pump	One piston pump Max operation pressure: 10 bar Max operation flow: 100 mL/min; Accuracy: 1.5% Pre-pump tubing: OD: 3.175 mm (1/8"); ID: 1 mm; PEEK; Post-pump tubing: OD: 1.6 mm (1/16"); ID: 0.75 mm; PEEK;	Two peristaltic pumps with the ability to add or remove one during construction. (i.e. 1 of the pumps is modular) Max operation pressure: 3 bar Max operation flow: 100 mL/min Accuracy: 1.5 % OD 4.8 mm, ID 1.6 mm, silicone tubing
Pressure sensor	Accuracy: 0.25%	Accuracy: 0.25%
In-loop air sensor	No	Modular. Designed so that the air sensor can be added or removed during construction
Flow direction valve	Rotary valves	Diaphragm valves
Post-column conductivity detector	Range: 0.02 – 200 mS/cm; Accuracy: ± 2%, min ± 20 µS/cm	Range: 0.3 – 300 mS/cm, Accuracy: ± 3% or 0.10 mS/cm
Post-column UV detector	1 wavelength (190–400 nm), variable Accuracy: ±1 nm	2 wavelength (190–400 nm), variable Accuracy: ±1 nm
Outlet valve	Rotary valves 8 inlets/1 outlet OD: 1.6 mm (1/16"); ID: 0.75 mm PTFE tubing	Diaphragm valves 8 inlets/1 outlet OD: 3.175 mm (1/8"); ID: 1.59 mm PTFE tubing
Bubble trap	No	No
Back pressure valve	Yes	Yes
Power supply	24 V connection into the unit. 110 V and 220 V to 24 V power bricks so unit can be plugged into wall socket.	24 V connection into the unit. 110 V and 220 V to 24 V power bricks so unit can be plugged into wall socket.
Fraction collector	No	Modular. Designed so that the fraction collector can be added or removed during construction.
Tubing	Before pump: ID 1 mm; After pump: ID 0.75 mm PEEK and PTFE non-pharm grade	ID 1.6 mm for all tubing PTFE and silicone Compliance with USP <88> Class IV or ISO 10993
Data outputs	CSV including the following information: Sample ID, column information, fraction id, retention time, plot of UV vs volume. Include any adjustable parameters Sample rate: 0.5 samples per second is acceptable	CSV including the following information: Sample ID, column information, fraction id, retention time, plot of UV vs volume. Include any adjustable parameters Sample rate: 0.5 samples per second is acceptable
Mixer	No	Yes
RFID compatibility (software)	Yes	Yes
Enclosure protective class	IP21	IP21

Got questions?

Get in touch for more information about product details, lead times or to request a quote.